

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche			
IVECO F32MNS	4	N	1750	10,9	Caprari BHR250A	1	250	250	Portata [lt/min]	10000	12000	14000
									Prevalenza [mt]	15	15	12
			1750	10,9	Caprari BHR200A	1	200	200	Portata [lt/min]	5000	6500	8000
									Prevalenza [mt]	25	24	21
			2000	11,4	Caprari AZH4/100A	1	125	100	Portata [lt/min]	2100	2400	2700
									Prevalenza [mt]	71	70	69
			2000	11,4	Caprari MR80/2A	2	100	80	Portata [lt/min]	1100	1500	1900
									Prevalenza [mt]	112	107	100
			2000	11,4	Caprari MG80/2A	2	100	80	Portata [lt/min]	1100	1500	1900
									Prevalenza [mt]	112	107	100
			2000	11,4	Caprari MR80-4/3C	3	100	80	Portata [lt/min]	1080	1200	1440
									Prevalenza [mt]	145	143	138
2000	11,4	Caprari MG80-4/3C	3	100	80	Portata [lt/min]	1080	1200	1440			
						Prevalenza [mt]	145	143	138			
IVECO N45MSAD	4	N	1750	11,1	Caprari BHR250A	1	250	250	Portata [lt/min]	10000	12000	14000
									Prevalenza [mt]	15	15	12
			1750	11,1	Caprari BHR200A	1	200	200	Portata [lt/min]	5000	6500	8000
									Prevalenza [mt]	25	24	21
			2000	11,6	Caprari AZH4/100A	1	125	100	Portata [lt/min]	2100	2400	2700
									Prevalenza [mt]	71	70	69
			2000	11,6	Caprari MR80/2A	2	100	80	Portata [lt/min]	1100	1500	1900
									Prevalenza [mt]	112	107	100
			2000	11,6	Caprari MG80/2A	2	100	80	Portata [lt/min]	1100	1500	1900
									Prevalenza [mt]	112	107	100
			2000	11,6	Caprari MR80-4/3C	3	100	80	Portata [lt/min]	1080	1200	1440
									Prevalenza [mt]	145	143	138
2000	11,6	Caprari MG80-4/3C	3	100	80	Portata [lt/min]	1080	1200	1440			
						Prevalenza [mt]	145	143	138			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
IVECO N45MSSA	4	T	2000	13,6	Caprari A3/125B	1	150	125	Portata [lt/min]	3000	3600	4800		
									Prevalenza [mt]	66	65	61		
			1750	13,1	Caprari A5/100B	1	125	100	100	100	Portata [lt/min]	2100	2700	3300
											Prevalenza [mt]	76	74	70
			2000	13,6	Caprari MR100/2H	2	125	100	100	100	Portata [lt/min]	2160	2400	2700
											Prevalenza [mt]	112	109	105
			2000	13,6	Caprari MG100/2H	2	125	100	100	100	Portata [lt/min]	2160	2400	2700
											Prevalenza [mt]	112	109	105
			2000	13,6	Caprari MR80-4/3B	3	100	80	80	80	Portata [lt/min]	1200	1700	2400
											Prevalenza [mt]	148	135	110
			2000	13,6	Caprari MG80-4/3B	3	100	80	80	80	Portata [lt/min]	1200	1700	2400
											Prevalenza [mt]	148	135	110
			1800	13,3	Caprari MR80-4/3A	3	100	80	80	80	Portata [lt/min]	1230	1720	2200
											Prevalenza [mt]	130	120	104
			1800	13,3	Caprari MG80-4/3A	3	100	80	80	80	Portata [lt/min]	1230	1720	2200
											Prevalenza [mt]	130	120	104
2200	14,3	Caprari MR80-1/3A	3	100	80	80	80	Portata [lt/min]	1080	1320	1600			
								Prevalenza [mt]	170	164	152			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche			
IVECO N67MSAE	6	N	2000	15	Caprari A3/125B	1	150	125	Portata [lt/min]	3000	3600	4800
									Prevalenza [mt]	66	65	61
			1750	14	Caprari A5/100B	1	125	100	Portata [lt/min]	2100	2700	3300
									Prevalenza [mt]	76	74	70
			2000	15	Caprari MR100/2H	1	125	100	Portata [lt/min]	2160	2400	2700
									Prevalenza [mt]	112	109	105
			2000	15	Caprari MG100/2H	2	125	100	Portata [lt/min]	2160	2400	2700
									Prevalenza [mt]	112	109	105
			2000	15	Caprari MR80-4/3B	2	100	80	Portata [lt/min]	1200	1700	2400
									Prevalenza [mt]	148	135	110
			2000	15	Caprari MG80-4/3B	3	100	80	Portata [lt/min]	1200	1700	2400
									Prevalenza [mt]	148	135	110
1800	14,3	Caprari MR80-4/3A	3	100	80	Portata [lt/min]	1230	1720	2200			
						Prevalenza [mt]	130	120	104			
1800	14,3	Caprari MG80-4/3A	3	100	80	Portata [lt/min]	1230	1720	2200			
						Prevalenza [mt]	130	120	104			
2200	15,5	Caprari MR80-1/3A	3	100	80	Portata [lt/min]	1080	1320	1600			
						Prevalenza [mt]	170	164	152			
IVECO N45MSTA 20.50	4	T	2000	16,8	Caprari AZRBH4/125C	1	150	125	Portata [lt/min]	3000	3600	4200
									Prevalenza [mt]	92	91	88
			1750	15,6	Caprari MR125/2G	2	150	125	Portata [lt/min]	3000	3600	3900
									Prevalenza [mt]	93	88	85
			2000	16,8	Caprari MR100/2F	2	125	100	Portata [lt/min]	2050	2400	3000
									Prevalenza [mt]	128	126	116
			2000	16,8	Caprari MG100/2F	2	125	100	Portata [lt/min]	2050	2400	3000
									Prevalenza [mt]	128	126	116
			1750	15,6	Caprari MR100/2B	2	125	100	Portata [lt/min]	1800	2040	2280
									Prevalenza [mt]	129	127	125
			1750	15,6	Caprari MG100/2B	2	125	100	Portata [lt/min]	1800	2040	2280
									Prevalenza [mt]	129	127	125
2000	16,8	Caprari MR100-1/2C	2	100	100	Portata [lt/min]	1680	1920	2160			
						Prevalenza [mt]	153	152	149			
2000	16,8	Caprari MG100-1/2C	2	100	100	Portata [lt/min]	1680	1920	2160			
						Prevalenza [mt]	153	152	149			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche			
N67MSTD23	6	T	1750	19,5	Caprari MR125/2E	2	150	125	Portata [lt/min]	3600	4200	4800
									Prevalenza [mt]	102	95	87
			1750	19,5	Caprari MR100/2A	2	125	100	Portata [lt/min]	2520	3000	3240
									Prevalenza [mt]	132	127	123
			1750	19,5	Caprari MG100/2A	2	125	100	Portata [lt/min]	2520	3000	3240
									Prevalenza [mt]	132	127	123
IVECO N67MNTA 20.00	6	T	2000	23,1	Caprari AZRBH4/125A	1	150	125	Portata [lt/min]	3000	3600	4200
									Prevalenza [mt]	115	114	111
			1750	21,9	Caprari MR125/2E	2	150	125	Portata [lt/min]	3000	3600	4200
									Prevalenza [mt]	106	102	95
			1750	21,9	Caprari MR100/2A	2	125	100	Portata [lt/min]	2050	2400	3000
									Prevalenza [mt]	137	133	127
			1750	21,9	Caprari MG100/2A	2	125	100	Portata [lt/min]	2050	2400	3000
									Prevalenza [mt]	137	133	127
			1750	21,9	Caprari MR100-2/3E	3	125	100	Portata [lt/min]	2520	2760	3000
									Prevalenza [mt]	151	147	141
			1750	21,9	Caprari MG100-2/3E	3	125	100	Portata [lt/min]	2520	2760	3000
									Prevalenza [mt]	151	147	141
IVECO N67ENTA 20.00	6	T	1750	27	Caprari MR125/2C	2	150	125	Portata [lt/min]	3600	3900	4200
									Prevalenza [mt]	119	117	114
			1600	25,2	Caprari MR125/3D	3	150	125	Portata [lt/min]	3000	3600	4200
									Prevalenza [mt]	138	130	122
			1750	27	Caprari MR100-2/3D	3	125	100	Portata [lt/min]	2520	3000	3480
									Prevalenza [mt]	159	150	137
			1750	27	Caprari MG100-2/3D	3	125	100	Portata [lt/min]	2520	3000	3480
									Prevalenza [mt]	159	150	137

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
IVECO F32MNS	4	N	2000	11,4	Rovatti S3P125K/M	1	125	100	Portata [lt/min]	2000	2500	2750	
									Prevalenza [mt]	65	63	61	
			2000	11,4	Rovatti F34P125K	1	125	100	100	Portata [lt/min]	2000	2500	2750
										Prevalenza [mt]	65	63	61
			2000	11,4	Rovatti S3K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	11,4	Rovatti F33K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	11,4	Rovatti S3K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	11,4	Rovatti F33K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	11,4	Rovatti S4K100-120/4E	4	100	80	80	Portata [lt/min]	1800	1600	1200
										Prevalenza [mt]	124	134	149
			2000	11,4	Rovatti F34K100-120/4E	4	100	80	80	Portata [lt/min]	1800	1600	1200
										Prevalenza [mt]	124	134	149
			2000	11,4	Rovatti S3K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400
										Prevalenza [mt]	162	145	124
2000	11,4	Rovatti F33K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400			
							Prevalenza [mt]	162	145	124			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
IVECO N45MSAD	4	N	2000	11,6	Rovatti S3P125K/M	1	125	100	Portata [lt/min]	2000	2500	2750	
									Prevalenza [mt]	65	63	61	
			2000	11,6	Rovatti F34P125K	1	125	100	100	Portata [lt/min]	2000	2500	2750
										Prevalenza [mt]	65	63	61
			2000	11,6	Rovatti S3K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	11,6	Rovatti F33K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	11,6	Rovatti S3K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	11,6	Rovatti F33K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	11,6	Rovatti S4K100-120/4E	4	100	80	80	Portata [lt/min]	1800	1600	1200
										Prevalenza [mt]	124	134	149
			2000	11,6	Rovatti F34K100-120/4E	4	100	80	80	Portata [lt/min]	1800	1600	1200
										Prevalenza [mt]	124	134	149
			2000	11,6	Rovatti S3K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400
										Prevalenza [mt]	162	145	124
2000	11,6	Rovatti F33K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400			
							Prevalenza [mt]	162	145	124			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
IVECO N45MSSA	4	T	2000	13,6	Rovatti S3P150K/L	1	150	125	Portata [lt/min]	3000	3500	4000		
									Prevalenza [mt]	74	72	69		
			2000	13,6	Rovatti F34P150K/L	1	150	125	125	125	Portata [lt/min]	3000	3500	4000
											Prevalenza [mt]	74	72	69
			1800	13,3	Rovatti S4K125/2M	2	125	100	100	100	Portata [lt/min]	2000	2500	2750
											Prevalenza [mt]	96	90	86
			1800	13,3	Rovatti F34K125/2M	2	125	100	100	100	Portata [lt/min]	2000	2500	2750
											Prevalenza [mt]	96	90	86
			1800	13,3	Rovatti S3K100/3E	3	100	80	80	80	Portata [lt/min]	1600	2000	2400
											Prevalenza [mt]	123	112	99
			1800	13,3	Rovatti F33K100/3E	3	100	80	80	80	Portata [lt/min]	1600	2000	2400
											Prevalenza [mt]	123	112	99
			2000	13,6	Rovatti S3K100/3G	3	100	80	80	80	Portata [lt/min]	1200	1600	200
											Prevalenza [mt]	150	143	134
			2000	13,6	Rovatti F33K100/3G	3	100	80	80	80	Portata [lt/min]	1200	1600	200
											Prevalenza [mt]	150	143	134
2000	13,6	Rovatti S4K100-120/4E	5	100	80	80	80	Portata [lt/min]	1200	1600	2000			
								Prevalenza [mt]	166	146	112			
2000	13,6	Rovatti F34K100-120/4E	5	100	80	80	80	Portata [lt/min]	1200	1600	2000			
								Prevalenza [mt]	166	146	112			
1750	13,1	Rovatti S4K100-160/5E	5	100	80	80	80	Portata [lt/min]	1800	2000	2200			
								Prevalenza [mt]	129	121	110			
1750	13,1	Rovatti F34K100-160/5E	5	100	80	80	80	Portata [lt/min]	1800	2000	2200			
								Prevalenza [mt]	129	121	110			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
IVECO N67MSAE	6	N	2000	15	Rovatti S3P150K/L	1	150	125	Portata [lt/min]	3000	3500	4000	
									Prevalenza [mt]	74	72	69	
			2000	15	Rovatti F34P150K/L	1	150	125	125	Portata [lt/min]	3000	3500	4000
										Prevalenza [mt]	74	72	69
			1800	14,3	Rovatti S4K125/2M	2	125	100	100	Portata [lt/min]	2000	2500	2750
										Prevalenza [mt]	96	90	86
			1800	14,3	Rovatti F34K125/2M	2	125	100	100	Portata [lt/min]	2000	2500	2750
										Prevalenza [mt]	96	90	86
			1800	14,3	Rovatti S3K100/3E	3	100	80	80	Portata [lt/min]	1600	2000	2400
										Prevalenza [mt]	123	112	99
			1800	14,3	Rovatti F33K100/3E	3	100	80	80	Portata [lt/min]	1600	2000	2400
										Prevalenza [mt]	123	112	99
			2000	15	Rovatti S3K100/3G	3	100	80	80	Portata [lt/min]	1200	1600	2000
										Prevalenza [mt]	150	143	134
2000	15	Rovatti F33K100/3G	3	100	80	80	Portata [lt/min]	1200	1600	2000			
							Prevalenza [mt]	150	143	134			
IVECO N45MSTA 20.50	4	T	2000	16,8	Rovatti S3P150K/H	1	150	125	Portata [lt/min]	3500	4000	4500	
									Prevalenza [mt]	86	85	83	
			1800	16,2	Rovatti S4K125/2I	2	125	100	100	Portata [lt/min]	2500	2750	3000
										Prevalenza [mt]	110	107	103
			1800	16,2	Rovatti F34K125/2I	2	125	100	100	Portata [lt/min]	2500	2750	3000
										Prevalenza [mt]	110	107	103
			1800	16,2	Rovatti S4K125/2G	5	125	100	100	Portata [lt/min]	2000	2250	2500
										Prevalenza [mt]	128	126	125
			1800	16,2	Rovatti F34K125/2G	5	125	100	100	Portata [lt/min]	2000	2250	2500
										Prevalenza [mt]	128	126	125
2000	16,8	Rovatti S4K100-120/5E	2	100	80	80	Portata [lt/min]	1200	1600	2000			
							Prevalenza [mt]	187	168	141			
2000	16,8	Rovatti F34K100-120/5E	2	100	80	80	Portata [lt/min]	1200	1600	2000			
							Prevalenza [mt]	187	168	141			



Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
IVECO N67MSTD23	6	T	1800	20,1	Rovatti S4K150/2L	2	150	125	Portata [lt/min]	3500	4000	4500		
									Prevalenza [mt]	104	100	92		
			1800	20,1	Rovatti F34K150/2L	2	150	125	125	125	Portata [lt/min]	3500	4000	4500
											Prevalenza [mt]	104	100	92
			1800	20,1	Rovatti S4K125/2E	2	125	100	100	100	Portata [lt/min]	2500	2750	3000
											Prevalenza [mt]	142	138	135
			1800	20,1	Rovatti F34K125/2E	2	125	100	100	100	Portata [lt/min]	2500	2750	3000
											Prevalenza [mt]	142	138	135
			2000	21	Rovatti S4K100-160/5E	5	100	80	80	80	Portata [lt/min]	2000	2400	2600
											Prevalenza [mt]	170	151	137
2000	21	Rovatti F34K100-160/5E	5	100	80	80	80	Portata [lt/min]	2000	2400	2600			
								Prevalenza [mt]	170	151	137			
IVECO N67MNTA 20.00	6	T	1800	22,8	Rovatti S4K150/2H	2	150	125	Portata [lt/min]	3000	3500	4250		
									Prevalenza [mt]	126	123	116		
			1800	22,8	Rovatti F34K150/2H	2	150	125	125	125	Portata [lt/min]	3000	3500	4250
											Prevalenza [mt]	126	123	116
			1800	22,8	Rovatti S4K125/3AM	3	125	100	100	100	Portata [lt/min]	2000	2500	3250
											Prevalenza [mt]	166	161	146
			1800	22,8	Rovatti F34K125/3AM	3	125	100	100	100	Portata [lt/min]	2000	2500	3250
											Prevalenza [mt]	166	161	146
IVECO N67ENTA 20.00	6	T	1600	25,2	Rovatti S4K150/3H	3	150	125	Portata [lt/min]	3500	4000	4500		
									Prevalenza [mt]	136	130	119		
			1600	25,2	Rovatti F34K150/3H	3	150	125	125	125	Portata [lt/min]	3500	4000	4500
											Prevalenza [mt]	136	130	119

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche			
DEUTZ F2M2011	2	N	2400	4,6	Caprari A3/65A	1	80	65	Portata [lt/min]	1000	1320	1680
									Prevalenza [mt]	57	54	46
			2400	4,6	Caprari HMU 50 2/4	3	80	50	Portata [lt/min]	660	780	1000
									Prevalenza [mt]	112	100	80
DEUTZ F3M2011	3	N	2400	6,8	Caprari A3/80A	1	100	80	Portata [lt/min]	1200	1800	2400
									Prevalenza [mt]	64	61	56
			2400	6,8	Caprari MR 65 3/2	2	80	65	Portata [lt/min]	960	1200	1440
								Prevalenza [mt]	83	87	79	
			2400	6,8	Caprari HMU 50 2/5	5	80	50	Portata [lt/min]	600	900	1140
								Prevalenza [mt]	144	113	79	
DEUTZ F4M2011	4	N	1750	7	Caprari BHR200A	1	200	200	Portata [lt/min]	5000	6000	9000
									Prevalenza [mt]	28	25	17
			2200	8,4	Caprari A4/100F	1	125	100	Portata [lt/min]	2100	2700	3300
									Prevalenza [mt]	58	56	51
			2200	8,4	Caprari A4/80A	1	100	80	Portata [lt/min]	1200	1800	2400
									Prevalenza [mt]	84	80	72
			2200	8,4	Caprari MR65-3/3A	3	80	65	Portata [lt/min]	1000	1320	1620
								Prevalenza [mt]	103	90	71	
			2200	8,4	Caprari MR65-2/4A	4	80	65	Portata [lt/min]	840	1080	1320
								Prevalenza [mt]	139	116	109	
DEUTZ BF4M2011	4	T	1750	9,7	Caprari BHR250	1	250	250	Portata [lt/min]	9000	12000	16000
									Prevalenza [mt]	21	19	13
			2000	10,6	Caprari AZH4/100A	1	125	100	Portata [lt/min]	1800	2400	3000
									Prevalenza [mt]	72	70	68
			2000	10,6	Caprari MR80/2A	2	100	80	Portata [lt/min]	1100	1680	2160
									Prevalenza [mt]	112	104	95
			2000	10,6	Caprari MG80/2A	3	100	80	Portata [lt/min]	1100	1680	2160
								Prevalenza [mt]	112	104	95	
			2000	10,6	Caprari MR80-4/3D	2	100	80	Portata [lt/min]	1100	1200	1400
								Prevalenza [mt]	140	139	133	
			2000	10,6	Caprari MG80-4/3D	3	100	80	Portata [lt/min]	1100	1200	1400
								Prevalenza [mt]	140	139	133	

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
DEUTZ BF4M2012	4	T	2000	13,4	Caprari A3/125A	1	150	125	Portata [lt/min]	3000	3600	4200	
									Prevalenza [mt]	70	70	68	
			2000	13,4	Caprari AH5/100B	1	125	100	100	Portata [lt/min]	2100	2700	3600
										Prevalenza [mt]	80	76	68
			2000	13,4	Caprari MR100/2H	2	125	100	100	Portata [lt/min]	2040	2400	2700
										Prevalenza [mt]	136	131	116
			2000	13,4	Caprari MG100/2H	2	125	100	100	Portata [lt/min]	2040	2400	2700
										Prevalenza [mt]	136	131	116
			2000	13,4	Caprari MR80-4/3C	3	100	80	80	Portata [lt/min]	1200	1700	2400
										Prevalenza [mt]	143	131	106
			2000	13,4	Caprari MG80-4/3C	3	100	80	80	Portata [lt/min]	1200	1700	2400
										Prevalenza [mt]	143	131	106
1800	12,7	Caprari MR80-4/3A	3	100	80	80	Portata [lt/min]	1230	1720	2200			
							Prevalenza [mt]	130	120	104			
1800	12,7	Caprari MG80-4/3A	3	100	80	80	Portata [lt/min]	1230	1720	2200			
							Prevalenza [mt]	130	120	104			
2200	13,7	Caprari MR80-1/3A	3	80	80	80	Portata [lt/min]	1080	1320	1600			
							Prevalenza [mt]	170	164	152			
DEUTZ BF4M2012C	4	T	2000	16,4	Caprari A3/125B	1	150	125	Portata [lt/min]	3000	4200	5400	
									Prevalenza [mt]	70	68	63	
			2000	16,4	Caprari AH5/100B	1	150	125	125	Portata [lt/min]	2100	2700	3000
										Prevalenza [mt]	114	111	110
			2000	16,4	Caprari MR100/2F	2	125	100	100	Portata [lt/min]	2040	2400	2700
										Prevalenza [mt]	128	126	120
			2000	16,4	Caprari MG100/2F	2	125	100	100	Portata [lt/min]	2040	2400	2700
										Prevalenza [mt]	128	126	120
2000	16,4	Caprari MR80/3A	3	100	80	80	Portata [lt/min]	1200	1920	2400			
							Prevalenza [mt]	164	145	132			
2000	16,4	Caprari MG80/3A	3	100	80	80	Portata [lt/min]	1200	1920	2400			
							Prevalenza [mt]	164	145	132			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
DEUTZ BF4M1013EC	4	T	1750	17,9	Caprari A4/125A	1	150	125	Portata [lt/min]	3000	4200	5400	
									Prevalenza [mt]	88	83	74	
			1750	17,9	Caprari MR100/2C	2	125	100	100	Portata [lt/min]	2750	3000	3500
										Prevalenza [mt]	112	109	101
			1750	17,9	Caprari MG100/2C	2	125	100	100	Portata [lt/min]	2750	3000	3500
										Prevalenza [mt]	112	109	101
			1750	17,9	Caprari MR100/2A	2	125	100	100	Portata [lt/min]	2040	2280	2520
										Prevalenza [mt]	137	135	132
			1750	17,9	Caprari MG100/2A	2	125	100	100	Portata [lt/min]	2040	2280	2520
										Prevalenza [mt]	137	135	132
DEUTZ BF6M2012C	6	T	2000	23,8	Caprari AZRBH4/125A	1	150	125	Portata [lt/min]	3600	4200	4800	
									Prevalenza [mt]	114	111	80	
			1750	22,8	Caprari MR125/2C	2	125	100	100	Portata [lt/min]	3000	3600	4200
										Prevalenza [mt]	123	119	114
			1750	22,8	Caprari MR100-2/3D	2	125	100	100	Portata [lt/min]	2500	3000	3250
										Prevalenza [mt]	159	150	144
			1750	22,8	Caprari MG100-2/3D	2	125	100	100	Portata [lt/min]	2500	3000	3250
										Prevalenza [mt]	159	150	144
DEUTZ B6M1013EC	6	T	2000	27,3	Caprari AZRBH4/125A	1	150	125	Portata [lt/min]	4800	5400	6000	
									Prevalenza [mt]	108	103	97	
			1750	25,2	Caprari MR125/2C	2	150	125	125	Portata [lt/min]	3200	3900	4800
										Prevalenza [mt]	121	117	107
			1750	25,2	Caprari MR100-2/3D	2	125	100	100	Portata [lt/min]	3240	3480	3720
										Prevalenza [mt]	144	137	129
DEUTZ F2M2011	2	N	2300	4,4	Rovatti S2P80K/E	1	80	65	Portata [lt/min]	1000	1200	1600	
									Prevalenza [mt]	50	47	41	
			2300	4,4	Rovatti S2K80/2G	2	80	65	65	Portata [lt/min]	1000	800	600
										Prevalenza [mt]	72	77	80
DEUTZ F3M2011	3	N	2300	6,7	Rovatti S3P105/G	1	100	80	Portata [lt/min]	1200	1800	2250	
									Prevalenza [mt]	59	55	48	
			2300	6,7	Rovatti S2K80/2E	2	80	65	65	Portata [lt/min]	1000	1200	1600
										Prevalenza [mt]	83	77	62
			2300	6,7	Rovatti S3K65/4F	4	65	50	50	Portata [lt/min]	400	600	800
										Prevalenza [mt]	144	124	99

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
DEUTZ F4M2011	4	N	2300	8,8	Rovatti S3P125/E	1	125	100	Portata [lt/min]	2000	2750	3300		
									Prevalenza [mt]	53	50	45		
			2300	8,8	Rovatti S3P105/E	1	100	80	80	80	Portata [lt/min]	1400	1800	2250
											Prevalenza [mt]	64	60	50
			2300	8,8	Rovatti S2K80/3E	3	80	65	65	65	Portata [lt/min]	800	1100	1400
											Prevalenza [mt]	120	110	95
DEUTZ BF4M2011	4	T	1600	8,9	Rovatti SN250	1	250	200	Portata [lt/min]	8000	11000	14000		
									Prevalenza [mt]	17	15	11		
			1800	10,2	Rovatti SN200G	1	200	150	150	150	Portata [lt/min]	5000	7000	9000
											Prevalenza [mt]	27	25	21
			2000	10,6	Rovatti S3P125K/M	1	125	100	100	100	Portata [lt/min]	2250	2750	3250
											Prevalenza [mt]	64	61	54
			2000	10,6	Rovatti F34P125K	1	125	100	100	100	Portata [lt/min]	2250	2750	3250
											Prevalenza [mt]	64	61	54
			2000	10,6	Rovatti S3K100/2G	2	100	80	80	80	Portata [lt/min]	1400	1800	2200
											Prevalenza [mt]	102	96	88
			2000	10,6	Rovatti F33K100/2G	2	100	80	80	80	Portata [lt/min]	1400	1800	2200
											Prevalenza [mt]	102	96	88
			2000	10,6	Rovatti S3K100H/3M	3	100	80	80	80	Portata [lt/min]	900	1000	1200
											Prevalenza [mt]	150	148	145
			2000	10,6	Rovatti F33K100/3M	3	100	80	80	80	Portata [lt/min]	900	1000	1200
											Prevalenza [mt]	150	148	145
			2000	10,6	Rovatti S4K100-120/4E	4	100	80	80	80	Portata [lt/min]	1200	1600	1800
											Prevalenza [mt]	149	134	124
2000	10,6	Rovatti F34K100-120/4E	4	100	80	80	80	Portata [lt/min]	1200	1600	1800			
								Prevalenza [mt]	149	134	124			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
DEUTZ BF4M2012	4	T	2000	13,4	Rovatti S3P150K/M	1	150	125	Portata [lt/min]	2750	3500	4250		
									Prevalenza [mt]	67	64	59		
			2000	13,4	Rovatti F34P150K/M	1	150	125	125	125	Portata [lt/min]	2750	3500	4250
											Prevalenza [mt]	67	64	59
			1800	12,7	Rovatti S4K125/2M	2	125	100	100	100	Portata [lt/min]	1800	2000	2500
											Prevalenza [mt]	98	96	90
			1800	12,7	Rovatti F34K125/2M	2	125	100	100	100	Portata [lt/min]	1800	2000	2500
											Prevalenza [mt]	98	96	90
			2000	13,4	Rovatti S3K100/3E	3	100	80	80	80	Portata [lt/min]	1400	1800	2200
											Prevalenza [mt]	131	122	110
			2000	13,4	Rovatti F33K100/3E	3	100	80	80	80	Portata [lt/min]	1400	1800	2200
											Prevalenza [mt]	131	122	110
			2000	13,4	Rovatti S4K100-120/5F	5	100	80	80	80	Portata [lt/min]	1200	1600	2000
											Prevalenza [mt]	166	146	112
			2000	13,4	Rovatti F34K100-120/5F	5	100	80	80	80	Portata [lt/min]	1200	1600	2000
											Prevalenza [mt]	166	146	112
			1750	12,4	Rovatti S4K100-160/5E	5	100	80	80	80	Portata [lt/min]	1800	2000	2200
											Prevalenza [mt]	129	121	110
1750	12,4	Rovatti F34K100-160/5E	5	100	80	80	80	Portata [lt/min]	1800	2000	2200			
								Prevalenza [mt]	129	121	110			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
DEUTZ BF4M2012C	4	T	2000	16,4	Rovatti S3P150K/I	1	150	125	Portata [lt/min]	4000	4500	5000	
									Prevalenza [mt]	79	73	69	
			2000	16,4	Rovatti F34P150K/I	1	150	125	125	Portata [lt/min]	4000	4500	5000
										Prevalenza [mt]	79	73	69
			1800	15,8	Rovatti S4K125/2I	2	125	100	100	Portata [lt/min]	2000	2500	3000
										Prevalenza [mt]	114	110	103
			1800	15,8	Rovatti F34K125/2I	2	125	100	100	Portata [lt/min]	2000	2500	3000
										Prevalenza [mt]	114	110	103
			2000	16,4	Rovatti S3K100H/3E	3	100	80	80	Portata [lt/min]	1200	1800	2400
										Prevalenza [mt]	167	156	136
			2000	16,4	Rovatti F33K100/3E	3	100	80	80	Portata [lt/min]	1200	1800	2400
										Prevalenza [mt]	167	156	136
			2000	16,4	Rovatti S4K100-160/4E	4	100	80	80	Portata [lt/min]	1600	2000	2200
										Prevalenza [mt]	146	137	129
			2000	16,4	Rovatti F34K100-160/4E	4	100	80	80	Portata [lt/min]	1600	2000	2200
										Prevalenza [mt]	146	137	129
			2000	16,4	Rovatti S4K100-120/5E	5	100	80	80	Portata [lt/min]	1200	1600	1800
										Prevalenza [mt]	187	168	141
2000	16,4	Rovatti F34K100-120/5E	5	100	80	80	Portata [lt/min]	1200	1600	1800			
							Prevalenza [mt]	187	168	141			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
DEUTZ BF4M1013EC	4	T	1800	18,1	Rovatti S3P150K/E	1	150	125	Portata [lt/min]	3500	4000	4500		
									Prevalenza [mt]	90	87	82		
			1800	18,1	Rovatti F34P150K/E	1	150	125	125	125	Portata [lt/min]	3500	4000	4500
											Prevalenza [mt]	90	87	82
			1800	18,1	Rovatti S4K125/2H	2	125	100	100	100	Portata [lt/min]	2000	2500	3000
											Prevalenza [mt]	121	119	114
			1800	18,1	Rovatti F34K125/2H	2	125	100	100	100	Portata [lt/min]	2000	2500	3000
											Prevalenza [mt]	121	119	114
			1800	18,1	Rovatti S4K125/2E	2	125	100	100	100	Portata [lt/min]	1800	2250	2500
											Prevalenza [mt]	144	142	140
			1800	18,1	Rovatti F34K125/2E	2	125	100	100	100	Portata [lt/min]	1800	2250	2500
											Prevalenza [mt]	144	142	140
			2000	19,7	Rovatti S4K100-160/5E	5	100	80	80	80	Portata [lt/min]	2000	2400	2600
											Prevalenza [mt]	170	151	137
2000	19,7	Rovatti F34K100-160/5E	5	100	80	80	80	Portata [lt/min]	2000	2400	2600			
								Prevalenza [mt]	170	151	137			
DEUTZ BF6M2012C	6	T	2000	23,8	Rovatti S3P150KG	1	150	125	Portata [lt/min]	3000	4000	5000		
									Prevalenza [mt]	95	92	85		
			2000	23,8	Rovatti S4K125/2AM	2	125	100	100	100	Portata [lt/min]	3000	3500	4000
											Prevalenza [mt]	131	124	113
			2000	23,8	Rovatti F34K125/2AM	2	125	100	100	100	Portata [lt/min]	3000	3500	4000
											Prevalenza [mt]	131	124	113
			1800	23,1	Rovatti S4K125/2E	2	125	100	100	100	Portata [lt/min]	2500	3000	3500
											Prevalenza [mt]	140	135	127
			1800	23,1	Rovatti F34K125/2E	2	125	100	100	100	Portata [lt/min]	2500	3000	3500
											Prevalenza [mt]	140	135	127
1800	23,1	Rovatti S4K125/3AM	3	125	100	100	100	Portata [lt/min]	2250	2500	3000			
								Prevalenza [mt]	164	161	152			
1800	23,1	Rovatti F34K125/3AM	3	125	100	100	100	Portata [lt/min]	2250	2500	3000			
								Prevalenza [mt]	164	161	152			



Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
DEUTZ B6M1013EC	6	T	1800	25,7	Rovatti S4K150/2G	2	150	125	Portata [lt/min]	3500	4000	4750	
									Prevalenza [mt]	128	124	116	
			1800	25,7	Rovatti F34K150/2G	2	150	125	125	Portata [lt/min]	3500	4000	4750
										Prevalenza [mt]	128	124	116
			1800	25,7	Rovatti S4K125/3AM	3	125	100	100	Portata [lt/min]	2500	3000	3500
										Prevalenza [mt]	161	152	140
			1800	25,7	Rovatti F34K125/3AM	3	125	100	100	Portata [lt/min]	2500	3000	3500
										Prevalenza [mt]	161	152	140

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
J. DEERE 4045 DF 150	4	N	1750	9,4	Caprari BHR250A	1	250	250	Portata [lt/min]	10000	12000	14000	
									Prevalenza [mt]	15	15	12	
			1750	9,4	Caprari BHR200A	1	200	200	200	Portata [lt/min]	5000	6500	8000
										Prevalenza [mt]	25	24	21
			2000	10,3	Caprari AZH4/100A	1	125	100	100	Portata [lt/min]	2100	2400	2700
										Prevalenza [mt]	71	70	69
			2000	10,3	Caprari MR80/2A	2	100	80	80	Portata [lt/min]	1100	1500	1900
										Prevalenza [mt]	112	107	100
			2000	10,3	Caprari MG80/2A	2	100	80	80	Portata [lt/min]	1100	1500	1900
										Prevalenza [mt]	112	107	100
			2000	10,3	Caprari MR80-4/3E	3	100	80	80	Portata [lt/min]	1100	1200	1400
										Prevalenza [mt]	135	134	129
2000	10,3	Caprari MG80-4/3E	3	100	80	80	Portata [lt/min]	1100	1200	1400			
							Prevalenza [mt]	135	134	129			
J. DEERE 6068 DF 150	6	N	2000	16,1	Caprari A3/125B	1	150	125	Portata [lt/min]	3000	3600	4800	
									Prevalenza [mt]	66	65	61	
			1750	14,5	Caprari A5/100B	1	125	100	100	Portata [lt/min]	2100	2700	3300
										Prevalenza [mt]	76	74	70
			2000	16,1	Caprari MR100/2H	2	125	100	100	Portata [lt/min]	2160	2400	2700
										Prevalenza [mt]	112	109	105
			2000	16,1	Caprari MG100/2H	2	125	100	100	Portata [lt/min]	2160	2400	2700
										Prevalenza [mt]	112	109	105
			2000	16,1	Caprari MR80-4/3B	3	100	80	80	Portata [lt/min]	1200	1700	2400
										Prevalenza [mt]	148	135	110
			2000	16,1	Caprari MG80-4/3B	3	100	80	80	Portata [lt/min]	1200	1700	2400
										Prevalenza [mt]	148	135	110
1800	14,8	Caprari MR80-4/3A	3	100	80	80	Portata [lt/min]	1230	1720	2200			
							Prevalenza [mt]	130	120	104			
1800	14,8	Caprari MG80-4/3A	3	80	80	80	Portata [lt/min]	1230	1720	2200			
							Prevalenza [mt]	130	120	104			
2200	16,8	Caprari MR80-1/3A	3	80	80	80	Portata [lt/min]	1080	1320	1600			
							Prevalenza [mt]	170	164	152			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche				
J. DEERE 6068 TF 150	6	T	2000	22,2	Caprari AZRBH4/125B	1	150	125	Portata [lt/min]	3000	3600	4200	
									Prevalenza [mt]	103	102	99	
			1750	20,4	Caprari MR125/2F	2	150	125	125	Portata [lt/min]	3600	3900	4200
										Prevalenza [mt]	95	91	87
			2000	22,2	Caprari MR100/2E	2	125	100	100	Portata [lt/min]	2400	3000	3300
										Prevalenza [mt]	134	126	123
			2000	22,2	Caprari MG100/2E	2	125	100	100	Portata [lt/min]	2400	3000	3300
										Prevalenza [mt]	134	126	123
			1750	20,4	Caprari MR100-2A	2	125	100	100	Portata [lt/min]	2040	2280	2520
										Prevalenza [mt]	137	135	132
			1750	20,4	Caprari MG100-2A	2	125	100	100	Portata [lt/min]	2040	2280	252
										Prevalenza [mt]	137	135	132
			2000	22,2	Caprari MR100-1/2B	2	100	100	100	Portata [lt/min]	1920	2160	2400
										Prevalenza [mt]	164	161	157
2000	22,2	Caprari MG100-1/2B	2	100	100	100	Portata [lt/min]	1920	2160	2400			
							Prevalenza [mt]	164	161	157			
J. DEERE 4045 DF 150	4	N	2000	10,3	Rovatti S3P125K/M	1	125	100	Portata [lt/min]	2000	2500	2750	
									Prevalenza [mt]	65	63	61	
			2000	10,3	Rovatti F34P125K	1	125	100	100	Portata [lt/min]	2000	2500	2750
										Prevalenza [mt]	65	63	61
			2000	10,3	Rovatti S3K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	10,3	Rovatti F33K100/2G	2	100	80	80	Portata [lt/min]	1600	1800	2000
										Prevalenza [mt]	99	96	92
			2000	10,3	Rovatti S3K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	10,3	Rovatti F33K100/3L	3	100	80	80	Portata [lt/min]	1000	1200	1400
										Prevalenza [mt]	130	127	123
			2000	10,3	Rovatti S3K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400
										Prevalenza [mt]	162	145	124
2000	10,3	Rovatti F33K80-90/6E	6	80	65	65	Portata [lt/min]	750	1100	1400			
							Prevalenza [mt]	162	145	124			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche					
J. DEERE 6068 DF 150	6	N	2000	16,1	Rovatti S3P150K/L	1	150	125	Portata [lt/min]	3000	3500	4000		
									Prevalenza [mt]	74	72	69		
			2000	16,1	Rovatti F34P150K/L	1	150	125	125	125	Portata [lt/min]	3000	3500	4000
											Prevalenza [mt]	74	72	69
			1800	14,8	Rovatti S4K125/2M	2	125	100	100	100	Portata [lt/min]	2000	2500	2750
											Prevalenza [mt]	96	90	86
			1800	14,8	Rovatti F34K125/2M	2	125	100	100	100	Portata [lt/min]	2000	2500	2750
											Prevalenza [mt]	96	90	86
			1800	14,8	Rovatti S3K100/3G	3	100	80	80	80	Portata [lt/min]	1600	2000	2400
											Prevalenza [mt]	123	112	99
			1800	14,8	Rovatti F33K100/3G	3	100	80	80	80	Portata [lt/min]	1600	2000	2400
											Prevalenza [mt]	123	112	99
2000	16,1	Rovatti S3K100/3E	3	100	80	80	80	Portata [lt/min]	1200	1600	2000			
								Prevalenza [mt]	150	143	134			
2000	16,1	Rovatti F33K100/3E	3	100	80	80	80	Portata [lt/min]	1200	1600	2000			
								Prevalenza [mt]	150	143	134			
2000	16,1	Rovatti S3K100/4H	4	100	80	80	80	Portata [lt/min]	1000	1600	2200			
								Prevalenza [mt]	155	146	119			
2000	16,1	Rovatti F33K100/4H	4	100	80	80	80	Portata [lt/min]	1000	1600	2200			
								Prevalenza [mt]	155	146	119			
J. DEERE 6068 TF 150	6	T	2000	22,2	Rovatti S3P150K/G	1	150	125	Portata [lt/min]	3500	4000	4500		
									Prevalenza [mt]	94	92	90		
			2000	20,7	Rovatti S4K125/2H	2	125	100	100	100	Portata [lt/min]	2750	3000	3250
											Prevalenza [mt]	117	114	110
			1800	20,7	Rovatti F34K125/2H	2	125	100	100	100	Portata [lt/min]	2750	3000	3250
Prevalenza [mt]	117	114									110			
1800	20,7	Rovatti S4K125/2F	2	125	100	100	100	Portata [lt/min]	2000	2250	2500			
								Prevalenza [mt]	135	133	131			
1800	20,7	Rovatti F34K125/2F	2	125	100	100	100	Portata [lt/min]	2000	2250	2500			
								Prevalenza [mt]	135	133	131			

Motore	N°cilindri	Asp	RPM	Consumo lt/h	Pompa	N° gir.	DNA	DNM	Prestazioni idrauliche			
15LD315	1	N	3300	1,8	Rovatti FL320	1	50	32	Portata [lt/min]	100	200	300
									Prevalenza [mt]	47	45	43
6LD435	1	N	2900	1,9	Rovatti FL420	1	60	40	Portata [lt/min]	200	350	500
									Prevalenza [mt]	50	45	34
3LD510	1	N	2900	2,1	Rovatti FL516	1	65	50	Portata [lt/min]	600	750	900
					Prevalenza [mt]				31	29	28	
			2900	2,1	Rovatti FL420/2I	2	50	40	Portata [lt/min]	200	300	400
					Prevalenza [mt]				65	62	57	
4LD640	1	N	2900	2,4	Rovatti FL516	1	65	50	Portata [lt/min]	600	900	1200
					Prevalenza [mt]				36	32	24	
			2900	2,4	Rovatti FL420/2H	2	50	40	Portata [lt/min]	200	300	400
					Prevalenza [mt]				72	69	65	
9LD626/2	2	N	2600	4,4	Rovatti F1L526F	1	65	50	Portata [lt/min]	700	900	1050
					Prevalenza [mt]				60	53	42	
			2600	4,4	Rovatti F1L526/2I	2	65	50	Portata [lt/min]	450	600	750
					Prevalenza [mt]				85	80	72	
LDW 1603	3	N	2600	5,1	Rovatti F2L626F	1	80	65	Portata [lt/min]	1000	1300	1600
					Prevalenza [mt]				60	56	50	
			2600	5,1	Rovatti F2L526/2G	2	65	50	Portata [lt/min]	600	750	900
					Prevalenza [mt]				95	87	75	
LDW 2204	4	N	2600	9,3	Rovatti F2L830I	1	100	80	Portata [lt/min]	1200	1800	2400
					Prevalenza [mt]				64	60	49	
			2600	9,3	Rovatti F2L626/2E	2	80	65	Portata [lt/min]	750	1000	1250
					Prevalenza [mt]				114	109	102	